



**Vintage Ceramic
Satin
LOW ODOR
STAIN RESISTANT
BN142 LINE**

| Type | Sheen | Spread Rate | Recommended Application | Thinner | Clean Up | DRY TIME | | |
|--|-------|--|-------------------------------------|-------------|------------------|------------|---------|---------|
| | | | | | | Tack Free | Re-coat | Cure |
| 100% Acrylic | Satin | 350 to 400 Sq Ft Per Gallon | Brush, Roller, Pad or Airless Spray | Clean Water | Warm Soapy Water | 30 Minutes | 4 Hours | 30 Days |
| PRODUCT NAME: Vintage Ceramic Satin | | Vintage Ceramic Satin is a 100% acrylic interior/exterior finish formulated with ceramic spheres to impart toughness and excellent stain resistance properties. The product is suitable for coating drywall, plaster, and masonry and primed wood or metal surfaces. The acrylic resin provides excellent color and gloss retention as well as tenacious adhesion properties. The ceramic spheres impart flow, leveling and stain removal characteristics. | | | | | | |
| WHERE TO USE: | | Drywall Plaster Wood Metal Masonry This acrylic satin wall and trim paint is a very low odor, low VOC product, making it perfect for homes, hospitals, schools, or any area where odor is a concern. It provides a tough satin finish for use in high abuse areas | | | | | | |
| Surface Preparation: | | <p>New Work: The surface to be coated must be clean and free of oil, grease, rust and other contaminants that could interfere with adhesion. Masonry surfaces should be fully cured.</p> <p>Priming: Surfaces must be clean, dry and dull. Remove rust and any loose or flaking paint. Vintage Ceramic is self-priming on drywall and cured plaster or masonry surfaces; prime bare wood or metal. If you need to coat metal, bleeding wood or over stains ask one of our Paint Professionals to recommend the appropriate primer.</p> <p>Repaint Work: Remove any oil, chalk, dirt, wax or dust prior to re-coating. Any loose or flaking paint should be removed, patched and the edges feather sanded to produce a smooth, uniform surface. Dull glossy surfaces to insure good adhesion. On previously painted surfaces in good repair, no priming is generally necessary. Spot prime bare areas with this product or the primer indicated above.</p> | | | | | | |
| Application: | | <p>Stir product with a circular, lifting motion to disperse into a homogenous liquid. To achieve proper results a quality 3/8" nap roller cover is required when using product containing ceramic microspheres.</p> <p>Brush – Nylon or polyester filament.</p> <p>Airless Spray – Tip at atomization pressures will vary with type of equipment, viscosity and temperature. An orifice of .011 - .017 will provide the most satisfactory spray pattern. Best results are more likely obtained by using quality application tools. Do not apply directly over chalky surfaces or bleeding stains.</p> | | | | | | |
| NOTE: Formulated without mercury or lead. | | | | | | | | |